

Notified Body pursuant to the Construction Products Regulation
Permission № CPR-26-NB2765/03.05.2018 of
Ministry of Regional Development and Public Works

Certificate of Constancy of Performance № 2765-CPR-0056

In compliance with Regulation (EU) № 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

Single-axis hinges

(the characteristics and the performances are described in Annex I which is an inseparable part of this certificate)

placed on the market under the name of

ÇUHADAROĞLU METAL SANAYİ VE PAZARLAMA A.Ş.
Yakuplu Mah. Hürriyet Bulvarı No: 6-8 Beylikdüzü / İstanbul

and produced in the manufacturing plant

Yakuplu Mah. Hürriyet Bulvarı No: 6-8 Beylikdüzü / İstanbul

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

EN 1935:2002

EN 1935:2002/AC:2003

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the
constancy of performance of the construction product

This certificate was first issued on 16.10.2018 and will remain valid until 04.02.2021 or neither the harmonised standard, the construction product, the assessment and verification of constancy of performance methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

04.02.2020

Manager of SZUTEST Ltd

Aşen Hacıoğlu

The validity of certificate can be traced on <http://public.szutest.com.tr/Certificate/Index>

The certificate will be reissued each year after annual surveillance audit

Notified Body pursuant to the Construction Products Regulation
 Permission № CPR-26-NB2765/03.05.2018 of
 Ministry of Regional Development and Public Works

Certificate of Constancy of Performance

№ 2765-CPR-0056

Annex I

Product: Lift-off hinges

Trade name: C60

Classification: 4 7 6 0 1 4 0 13

A hinge for use in severe duty situations tested to 200 000 cycles, for use on doors with a mass up to 120 kg, with no stated fire resistance, very high corrosion resistance, not suitable for use on burglar resistant doors, and with a hinge grading of 13.

Trade name: 40 D 27

Classification: 1 4 3 0 1 4 0 9

A hinge for use in light duty situations tested to 25 000 cycles, for use on doors or windows with a mass up to 60 kg, with no stated fire resistance, very high corrosion resistance, not suitable for use on burglar resistant doors and windows and with a hinge grading of 9.

Trade name: 40 D 22

Classification: 1 4 2 0 1 4 0 6

A hinge for use in light duty situations tested to 25 000 cycles, for use on doors or windows with a mass up to 40 kg, with no stated fire resistance, very high corrosion resistance, not suitable for use on burglar resistant doors and windows and with a hinge grading of 6.

Essential Characteristics	Performance	Harmonized standard
Self closing	Safety: Initial Frictional torque – Pass Static load – Pass Overload – Pass Shear strength – N/A	EN 1935:2002 EN 1935:2002/AC:2003
Durability	Suitability for use on fire/smoke doors: Fire/smoke suitability – NPD Pass/fail criteria for: Durability: Durability – Pass Corrosion resistance: Corrosion grade – Pass	
Dangerous substances	NPD	

04.02.2020

Manager of SZUTEST Ltd

Asen Hristov

The validity of certificate can be traced on <http://public.szutest.com.tr/Certificate/Index>

The certificate will be reissued each year after annual surveillance audit Page 1 of 1